ROWELD® type Premium CNC

Hydraulic butt-welding machine Ø 90 - 630 mm

The Premium CNC System enables a nearly fully automated operation. All parameters are documented automatically

Product Profile

APPLICATION AREA

The ROWELD® Hydraulic Premium CNC with integrated CNC control and touch screen panel for the quick and reliable saving of the welding parameters in accordance with DVS and other applicable international guidelines and standards. Data transfer via USB interface

WORKING RANGE			
Model	Ø mm	Ø Inch	
P 250 B SA / P 8 B SA	90 - 250 mm	5 - 8"	
P 250 B VA / P 8 B VA	90 - 250 mm	5 - 8"	
P 355 B SA / P 12 B SA	90 - 355 mm	5 - 12"	
P 500 B SA / P 18 B SA	200 - 500 mm	8 - 18"	
P 630 B SA / P 24 B SA	315 - 630 mm	12 - 24"	
P1200 B SA / P 48 B SA	710 - 1,200 mm	22 - 48"	

SA = semi-automatic, VA = fully automatic



TECHNICAL DATA

Logging:

Automatic logging: 10,000 logs **Data output:** USB interface

Languages: DE, EN, FR, ES, NL, PT, DK, SE, NO, FI, PL, TR,

HU, SL, SK, RU, BG, futher languages available

upon request

Welding monitoring: Optically with colour indication for welding

pressure, welding temperature, welding times, as well as acoustical and optical for user actions

in accordance to DVS

Welding standards: DVS, further standards available upon request,

manual entry of welding parameters is possible

With CNC function: During the welding process, all movements

are performed by the machine, including dragging resistance and bead development measurement. Automatic extending heading element enables a fully-automatic welding

process (optional, not available for all machines)

